

FOR FUTURE USE AND REFERENCE
RETAIN THIS INSTRUCTION SHEET AND THE CRIB TOOLS IN THE ORIGINAL SACK
AND SECURE IT TO THE SPRING UNDER THE MATTRESS WITH PLASTIC TIES.

CARE INSTRUCTIONS: The natural warmth of wood is a lasting value. Character marks, checking and grain variations are part of the beauty of wood and, therefore, should not be a concern. If treated with care, this solid wood product will last you for many years to come. Once every week, wipe your Baby's Dream furniture with Pledge®, lemon oil or other similar wood treatment products. If you encounter any roughness in the finish of your new crib, fold a piece of regular white paper—not tissue or newspaper—and rub it gently against the surface until the desired smoothness is achieved. If refinishing, use a non-toxic finish specified for children's products. Let dry, sand with a very fine product such as folded paper or dish washing sponge and, finally, apply water-based baby-safe lacquer for the perfect matching shine.

WARNING! To insure your child's safety and for your own peace of mind, be sure to follow instructions properly. Failure to follow these warnings and assembly instructions could result in serious injury or death. Before each usage or assembly, inspect the crib for damaged hardware, loose joints, missing parts or sharp edges.


- ✓ **DO NOT** use the crib if any parts are missing or broken.
- ✓ **DO NOT** substitute parts. Ask your dealer or write to Baby's Dream Furniture for replacement parts and instructional literature if needed.
- ✓ Make sure that all bolts and screws are properly tightened. **DO NOT** over- or under-tighten.
- ✓ **AVOID STRANGULATION:** As soon as an infant can sit or stand up, close the crib gate or raise the Drop Front permanently.
- ✓ **DO NOT** place the crib near a window where cords from blinds or drapes may strangle a child.
- ✓ **DO NOT** tie pacifiers, necklaces or any other items around a child's neck or on the crib parts.

WARNING! Strings can cause strangulation! Do not place items with string around a child's neck, such as hood strings or pacifier cords. Do not suspend strings over a crib or attach string toys.

- ✓ **NEVER** use plastic shopping bags or other film as mattress covers, because they can cause suffocation.
- ✓ For a newborn, adjust the spring on the highest level of the Height Adjuster and open the gate or lower the Drop Front for easy access.
- ✓ **DO NOT** leave a child in a crib with an open gate or lowered Drop Front. Be sure the gate is closed or the Drop Front is raised and locked in position whenever the child is in the crib. After closing the gate or raising the Drop Front, make sure the latches are secure.
- ✓ The child must be seated at the rear of the crib when lowering or raising the gate or Drop Front.
- ✓ As your child grows, adjust the height of the spring down so that he/she cannot pull himself/herself out of the crib. When the child is able to pull to a standing position, set the mattress to the lowest position and remove bumper pads, large toys and other objects that could serve as steps for climbing out. When the child is able to climb out or reaches the height of 35" (90cm), the bed should no longer be used in the form of a crib. You can continue to use this crib as a youth or toddler bed for another 2 to 3 years by using the **Youth Bed Conversion Kit**.

ANY MATTRESS USED IN THIS CRIB MUST BE AT LEAST 27 1/4" X 51 5/8" WITH A THICKNESS NOT EXCEEDING 6". DO NOT USE A WATER MATTRESS WITH THIS CRIB.

This crib conforms to the applicable regulations promulgated by the Consumer Product Safety Commission.




This product may be covered by one or more of the following patents: D366,778; D366,970,5,077,846 and other patents pending.



BABY'S DREAM
FURNITURE, INC.


Buena Vista, GA 31803-0579
 www.babysdream.com



Convertible "Set 4 Life™" Instruction Sheet
 Read All Instructions Before Assembling Crib. Keep Instructions For Future Use.

PARTS LIST (A PHILLIPS HEAD SCREWDRIVER AND A FLAT-HEAD SCREWDRIVER IS REQUIRED)

BF) 1	Back Frame (largest; attached to Cap rail)	MS) 1	Mattress Support (metal spring)
FF) 1	Front Frame (with the Drop Gate)	B80) 16	80 Millimeter Bolts
DG) 1	Drop Gate (attached to Front Frame)	B1) 4	Small 1" Spring Bolts
SF) 2	Side Frame	AW) 1	Allen Wrench (included)
FP) 2	Front Corner Posts (with Strike Plate)	HW) 1	Hex Wrench (included)
RP) 2	Rear Corner Posts (without Strike Plate)	TL) 2	Trigger Latch (attached to Drop Gate)
SH) 2	Short Post (without Strike Plate)	SP) 2	Strike Plates (attached to Front Corner Post)
YBK) 1	Youth Bed Kit	HA) 4	Height Adjusters (attached to 4 Corner Posts)
CAP) 1	Cap Rail for Foot Board	H) 3	Hinges (attaches Drop Gate to Front Frame)
DW) 7	Wooden Dowels	ABR) 2	Crib 4 Life Wooden Adult Bed Rails (not included with the Crib), or regular bolt-on metal rails.
GP) 4	Gate Pins		




BF) Back Frame



FF) Front Frame




SF) Side Frame



RP) Rear Corner Posts

FP) Front Corner Posts

SH) Short Posts



HW) Hex Wrench




TL) Trigger Latch



AW) Allen Wrench



SP) Strike Plate



MS) Mattress Support



80mm Bolt



GP) 1 1/4 inch Gate Pin




DW) Dowel



B1) Small Spring Bolts



Youth Bed Kit



ABR) Adult Bed Rails




ABR End View

CRIB ASSEMBLY INSTRUCTIONS

Step 1: Lay the Back Frame (BF) on the floor, and attach a Rear Corner Post (RP) to the Back Frame (BF) using two 80mm Bolts (B80).

Step 2: Repeat Step 1 for the other side of the Back Frame (BF) to attach the other Rear Corner Post (RP) using two 80mm Bolts (B80).



Step 3

Step 4: Repeat Step 3 for the other side of the Front Frame (FF) using two 80mm Bolts (B80). Before fully tightening bolts, stand the Front assembly up to let the Front Frame (FF) drop to the bottom of the holes. Make sure that the posts do not stick above the frames. Now is the time to tighten all bolts.


Step 5: Use two 60mm Bolts (B60) to attach one Side Frame (SF) to the Rear Corner Post (RP). Using two more 60mm Bolts (B60) attach the Side Frame (SF) to the Front Corner Post (FP).

Step 6: Make a 4 sided crib by repeating Step 5 for the other side.



Step 7

WARNING: To properly open and close the Drop Gate both trigger latches must be fully depressed. Failure to do so may result in personal injury and/or damage to crib. Do not slam the gate to close.



Step 1 & 2

Step 3: Place the Front Frame (FF) on the floor, and attach the Front Corner Post (FP) to the Front Frame (FF) using two 80mm Bolts (B80). Make sure that the top of the Drop Gate (DG) is flush with the top of the Front Corner Post (FP). Do not fully tighten the bolts at this time.



Step 4 & 5

Step 7: Lower the Mattress Support Spring (MS) into the crib and attach to the crib by tightening 4 Small Bolts (B1) into the adjustment inserts in the desired position.

*Note: The gate swings down to the outside of the crib.



Once a crib has been converted to a youth bed or adult bed it is not intended to be converted back to a crib.

YOUTH BED ASSEMBLY INSTRUCTIONS

STARTING FROM CRIB:

Step 1: Remove the Front Frame (FF) (and Drop Gate) from the crib. Leave the Front Corner Posts (FP) on.

Step 2: Make sure that the Mattress Support Spring (MS) is at the lowest level of the Height Adjuster (HA).

Step 3: Attach the Youth Bed Kit (YBK) to the Front Corner Posts (FP) with two 80mm Bolts (B80).

Step 4: Remove the Strike Plates (SP) from the Front Corner Posts (FP).

STARTING FROM SCRATCH:

Step 1: Follow steps 1 through 6 of the Crib assembly instructions.

Step 2: Remove the Front Frame (FF) and Drop Gate (DG) from the crib.

Step 3: Follow steps 2 through 4 of the above Youth Bed assembly instructions (starting from crib).



YOUTH BED

YOUTH BED GUARD RAIL INSTRUCTIONS

Step 1: Use the above instructions to convert your Set 4 Life™ into a Youth Bed.

Step 2: Unscrew the hinge or hinges that attach the Drop Gate (DG) to the Front Frame (FF). Detach the Drop Gate (DG).

Step 3: Detach the 2 Trigger Latches (TL) from both ends of the Drop Gate (DG).

Step 4: Hammer in the Gate Pins (GP) 3/4 inches into the pilot holes on the two ends of the Drop Gate (DG).

Step 5: Loosen the two 80mm Bolts (B80) that are used to bolt up the Youth Bed Kit (YBK).

Step 6: Insert the Gate Pins (GP) located in the ends of the Drop Gate (DG) into the holes located in the Front Posts (FP).

Step 7: Tighten the bolts that bolt-up the Youth Bed Kit (YBK).



FULL SIZE BED ASSEMBLY INSTRUCTIONS

Step 1: Remove the Drop Gate (DG) from the Front Frame (FF) by unscrewing the 3 Hinges (H).

Step 2: Remove the two Strike Plates (SP) from the Front Corner Posts (FP).

Step 3: Remove all 4 Height Adjusters (HA) from all four Corner Posts.

Step 4: Place the Back Frame (BF) on the floor and connect 2 Rear Corner Posts (RP) with 80mm Bolts (B80).

Step 5: Place the Front Frame (FF) on the floor and connect 2 Short Corner Posts (SP) with 80mm Bolts (B80). Make sure that the Front Frame (FF) is turned upside down and dowel holes are on the top.



DOUBLE BED

Step 6: Attach the Cap Rail (CAP) to Front Frame (FF), which is now the foot board. Wet the Dowels (DW) and fit them inside the holes of Cap Rail and Front Frame.

Step 7: Connect the head board and the foot board with a metal bed rail. Use regular 1/4-20 nuts & bolts. You can use Baby's Dream Furniture's matching solid wood Adult Bed Rails (ABR). If you're using matching wooden ABRs, make sure that the mattress support cleats are on the upper end of the rails, and you can dispose of the extra Short Posts meant for Crib 4 Life™.